

## MT 24 N - MT 26 N commercial freestanding safes "Karat"

### RESISTANCE GRADE N

- type tested and supervised security by ECB-S
  - protected against burglary and fire
  - body triple-walled, exterior walls of flame-cutting protected stainless steel material
  - double-walled door with additional armouring, door leaf thickness 7 mm SM steel
  - three-sided locking through strong square bolts, bolts on the top and on the bottom with integrated steel rolls - extreme protection against flame-cutting, drilling and attack, all-over gripping hinge
  - prepared for wall and floor fixing, with fixing material - extreme high breaking strength
  - fire-protective material in body and door, specially designed fire fold
  - depth for files of common size, 1 adjustable shelf
- security advantage:**
- special protection against drilling
  - thermal emergency locking mechanism



MT 24 N S



### Version S

Resettable, armoured high-security safe lock, 'Secu-Safe', ECB-S certified according to EN 1300 class B, with 2 keys, 10 levers, key captive, 50,000,000 different combinations. More security in case of losing the key – immediately resettable to a new key.

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	mm	kg	l
<b>MT 24 N S</b>	16050 3	340 x 430 x 390	250 x 348 x 294	250 x 336	43	25,8
<b>MT 26 N S</b>	19090 6	530 x 430 x 390	440 x 348 x 294	440 x 336	60	45,3



### Version E

Electronic combination lock 'SecuTronic', ECB-S certified according to EN 1300 class B, with intelligent menu-driven operation, administration of up to 10 users, 111,000,000 different combinations possible, incl. batteries. The locking armature protrudes 16 mm.

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	mm	kg	l
<b>MT 24 N E</b>	19150 7	340 x 430 x 390	250 x 348 x 294	250 x 336	43	25,8
<b>MT 26 N E</b>	19020 3	530 x 430 x 390	440 x 348 x 294	440 x 336	60	45,3



MT 24 N E

## Information about Locking Systems



### Version S: (from Resistance Grade N)

- high-security safe lock 'Secu-Safe'
- ECB-S certified according to EN 1300 class B, for Resistance Grade N (0) to V, 10 levers, key captive, 50,000,000 different combinations
- more security in case of losing the key - immediately resettable to a new key
- resetting several safes to a common key is easily possible
- the innovative technology of these locks offers an extraordinary high protection against manipulation, strength against violent attacks and a maximum life



### Version C:

- resettable, mechanical combination lock 'SECUMATIC', ECB-S certified according to EN 1300 class B
- digital combination lock - easy to handle, 1,000,000 different combinations possible
- resetting without any problem, digits engage perceptibly
- available for commercial freestanding safes series Diplomat



### Version E: (from Resistance Grade N)

- electronic combination lock 'SecuTronic', ECB-S certified according to EN 1300 class B, incl. batteries
- 111,000,000 different combinations possible, 6- to 8- digit secret code
- resettable at any time without any problems
- for up to 10 users
- with protection against manipulation
- batteries can be exchanged from the outside, no loss of code without batteries
- with integrated time function
- as a series with opening delay (from 0-99 minutes)



MT 26 N E

BURG-WÄCHTER safes correspond to the highest state-of-the-art technology and are internationally recognized. Changes in dimensions and constructions of wall safes and freestanding home safes can occur due to technical production changes.



C 1 S

## Freestanding home safes CityLine

### SECURITY LEVEL B

- security level B according to VDMA 24992, 5/95
- double-walled
- fire-protective material according to DIN 4102-A1
- possibility to anchor the safe through the back wall
- effective locking mechanism
- specially designed fire fold
- for files of common size



C 1 E



### Version S

Security safe lock 'Secu-Safe', ECB-S certified according to EN 1300 class A, with 2 keys, 9 levers, more than 1,000,000 different combinations.

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	mm	kg	l
C 1 S	14880 8	320 x 420 x 376	243 x 343 x 294	243 x 333	33,5	24,5
C 4 S	14070 3	528 x 435 x 382	440 x 350 x 292	440 x 345	49,0	45,3



C 4 E



### Version E

Electronic combination lock 'SecuTronic', ECB-S certified according to EN 1300 class B, 1,000,000 different combinations possible, incl. batteries. The locking armature protrudes 13 mm.

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	mm	kg	l
C 1 E	26490 4	320 x 420 x 376	243 x 343 x 294	243 x 333	33,5	24,5
C 4 E	14080 2	528 x 435 x 382	440 x 350 x 292	440 x 345	49,0	45,3



H 1 S



### Version S

Security safe lock 'Secu-Safe', ECB-S certified according to EN 1300 class A, with 2 keys, 9 levers, more than 1,000,000 different combinations.

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	mm	kg	l
H 1 S	14900 3	320 x 420 x 376	243 x 343 x 294	243 x 333	33,5	24,5



H 1 E



### Version E

Electronic combination lock 'SecuTronic', ECB-S certified according to EN 1300 class B, 1,000,000 different combinations possible, incl. batteries. The locking armature protrudes 13 mm.

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	mm	kg	l
H 1 E	26290 0	320 x 420 x 376	243 x 343 x 294	243 x 333	33,5	24,5

BURG-WÄCHTER safes correspond to the highest state-of-the-art technology and are internationally recognized. Changes in dimensions and constructions of wall safes and freestanding home safes can occur due to technical production changes.